

HIGH PRESSURE Regulating Unloader



Model
7576

Ideal for heavy equipment washdown, rubber, rust or paint removal, injection and blast cutting applications.

Heavy-Duty High Pressure System Pressure Relief and Protection

- Pressure setting from 1500 to 7250 PSI.
- Relieves full pressure at pump while in by-pass and gradually builds to high pressure when system resumes operation.
- Full pressure regulation with either single or multiple pumps, multiple nozzles, solenoid or gate valve systems.

SPECIFICATIONS

	U.S. Measure	Metric Measure
Flow Range.....	1 to 21 GPM	3.8 to 80 L/M
Maximum Pressure	1500 to 7250 PSI	105 to 500 BAR
Maximum Temperature.....	195°F	90°C
Inlet Port (Back)	1/2" BSPF	1/2" BSPF
Outlet Port (Front)	1/2" BSPF	1/2" BSPF
By-pass Port (Side)	1/2" BSPF	1/2" BSPF
Gauge Port	1/4" BSPF	1/4" BSPF
Weight	7.6 lbs	3.45 kg
Dimensions	9.23 x 5 x 2.85"	234.5 x 127x 72.5 mm



www.catpumps.com • email: techsupport@catpumps.com

1681 - 94th Lane NE, Minneapolis, MN 55449-4324 • Phone: 763-780-5440 • Fax: 763-780-2958



The Pumps with Nine Lives