

MODEL 67102C PLUNGER PUMP



100 GPM | 1,000 PSI

Designed for Central Cleaning Systems

Cat Pumps model 67102C is designed for high-flow applications demanding superior dependability and long life.

Cat Pumps engineers focused on every critical design element to produce a pump with incredible service life. The heavy-duty cast duplex stainless steel manifolds stand up to the most demanding, continuous duty applications. The drive-end uses matched connecting rods and oversized bearings to provide thousands of hours of trouble-free service. Concentric, high-density polished solid ceramic plungers provide a true wear surface, resulting in industry-leading seal life.

The 67102C is what you expect from Cat Pumps — a high-quality, dependable product backed by the industry's best customer service and support.

Features:

- 85% overall efficiency, provides substantial energy savings compared to Pitot Tube Pumps' 45–60% efficiency
- Seal flush version, 67102C, permits external flush for added cooling when high-temperature fluid is required
- Long duration between servicing
- Can be conveniently and easily serviced in place, in a fraction of the time and at a much lower cost compared to Pitot Tube Pumps

Typical Applications:


- Central Cleaning Systems in Food Processing
- Multi-Gun Washdown Systems
- Heavy-Duty Mobile Equipment Washdown
- High-Flow and Pressure Chemical Processing
- Wastewater Treatment and Reclamation
- Salt and Brackish Water Desalination (SWRO)

Specifications

	US MEASURE	METRIC MEASURE
Flow	100 gpm	378.5 lpm
Pressure	1000 psi	69 bar
Pump RPM*	680	680
Inlet Pressure Range	Flooded to 30 psi	Flooded to 2 bar
Max. Liquid Temperature	180° F	82° C
Crankcase Capacity	10 qts	9.46 l
Inlet Ports (2)	2 ½" NPT(F)	2 ½" NPT(F)
Flush Ports (2)	¼" NPT(F)	¼" NPT(F)
Discharge Ports (2)	2" NPT(F)	2" NPT(F)
Shaft Diameter	1.772"	45 mm
Weight	363.75 lbs	165 kg
Dimensions	30.04 x 24.37 x 12.67"	763 x 619 x 322 mm

*Pump minimum is 100 RPM.

Dimensions



Popular Accessories



Pressure Regulator

PN 7410
10–100 GPM
100–1,500 psi



Pop-Off Valve

PN 890710
0–100 gpm
300–1500 psi



Pressure Gauge

PN 6073
0–3,000 psi



Pulsation Dampener

PN 701557
320 gpm
1,275 psi



Oil

PN 6102
2.5 gallons
Specially formulated for
extended protection

Contact Cat Pumps for more information at info@catpumps.com or (763) 780-5440



CAT PUMPS

1681 94TH LANE N.E. MINNEAPOLIS, MN 55449-4324
PHONE (763) 780-5440 | FAX (763) 780-2958
E-MAIL: INFO@CATPUMPS.COM
WWW.CATPUMPS.COM